

Thermodyne's 1600NDNL provides food quality and kitchen efficiency like no other piece of equipment on the market today. Using patented Fluid Shelf® technology each shelf in the cabinet maintains an exact temperature, allowing for extended holding times, without sacrificing appearance or taste. Units are available as pass through or with a solid panel back and include our exclusive removable floating lid system.

SPECIFICATIONS	
UPPER	
EXTERIOR DIMENSIONS	17.50"W x 23.00"D x 25.88"H
INTERIOR DIMENSIONS	13.50"W x 22.00"D x 20.25"H
CUBIC CAPACITY	3.48ft ³
LOWER	
EXTERIOR DIMENSIONS	17.50"W x 33.00"D x 35.87"H
INTERIOR DIMENSIONS	13.50"W x 22.00"D x 29.38"H
CUBIC CAPACITY	5.05ft ³
MAX OPERATING TEMP	230°F
NET WEIGHT	241lbs.
SHIPPING WEIGHT	405lbs.

ELECTRICAL SPECIFICATIONS	
VOLTS	208 / 240
AMPS	25 / 29
TOTAL WATTS	5250 / 7000
HERTZ	60
PHASE	1
PLUG	NEMA L14-30

SHELVES	
STANDARD	9

CAPACITY*	
STEAM TABLE PAN	
12" x 20" x 2.5"	5
12" x 20" x 6"	4

*Total standard capacity based on both 2.5" and 6" pans.

OPTIONS / ACCESSORIES	
Protective Bumper Base	Additional Heat Transfer Plates
Controller Shield	Solid Stainless Steel Doors
Solid Back Panel	Stainless Steel Drip Pan

Specifications subject to change without notice.

Upper exterior height includes .13"H middle divider.

