

Thermodyne's 1600NDNL provides food quality and kitchen efficiency like no other piece of equipment on the market today. Using patented Fluid Shelf® technology each shelf in the cabinet maintains an exact temperature, allowing for extended holding times, without sacrificing appearance or taste. Units are available as pass through or with a solid panel back and include our exclusive removable floating lid system.



| SPECIFICATIONS | |
|---------------------|-----------------------------|
| UPPER | |
| EXTERIOR DIMENSIONS | 17.50"W x 23.00"D x 25.88"H |
| INTERIOR DIMENSIONS | 13.50"W x 22.00"D x 20.25"H |
| CUBIC CAPACITY | 3.48ft ³ |
| LOWER | |
| EXTERIOR DIMENSIONS | 17.50"W x 33.00"D x 35.87"H |
| INTERIOR DIMENSIONS | 13.50"W x 22.00"D x 29.38"H |
| CUBIC CAPACITY | 5.05ft ³ |
| MAX OPERATING TEMP | 230°F |
| NET WEIGHT | 241lbs. |
| SHIPPING WEIGHT | 405lbs. |

| ELECTRICAL SPECIFICATIONS | |
|---------------------------|-------------|
| VOLTS | 208 / 240 |
| AMPS | 25 / 29 |
| TOTAL WATTS | 5250 / 7000 |
| HERTZ | 60 |
| PHASE † | 1 |
| PLUG | NEMA L14-30 |

| SHELVES | |
|----------|---|
| STANDARD | 9 |

| CAPACITY* | |
|------------------|---|
| STEAM TABLE PAN | |
| 12" x 20" x 2.5" | 5 |
| 12" x 20" x 6" | 4 |

*Total standard capacity based on both 2.5" and 6" pans.

| OPTIONS / ACCESSORIES | |
|------------------------|---------------------------------|
| Protective Bumper Base | Additional Heat Transfer Plates |
| Controller Shield | Solid Stainless Steel Doors |
| Solid Back Panel | Stainless Steel Drip Pan |

† Available in 3Ø by request

Specifications subject to change without notice.
 Upper exterior height includes .13"H middle divider.

